



SafetyLink®
Innovative
Fall Protection



RafterLink™

Rafter Mounted Anchor

SafetyLinks RafterLink can be purchased in a variety of configurations.



SafetyLink RafterLink



SafetyLink
Side Mounted RafterLink



SafetyLink
RafterLink (75mm raised)



SafetyLink RidgeLink



SafetyLink RafterLink with Rhino Steel

Tiled Roof Anchor

- Designed for use on timber structures where there is easy access to the underside of the roof.
- Can be used for abseiling if installed with a SafetyLink Abseil Eyebolt.
- Multi-directional fall protection.
- Complies with AS/NZS 1891.4.
- Single person roof anchor, rated at 15kN.



SafetyLink®
Innovative
Fall Protection

SafetyLink Pty Ltd **1300 789 545**
+61 2 4964 1068 info@safetylink.com

**'Innovative
Fall Protection'**

For further information and to order our products visit our website.

www.safetylink.com



SafetyLink®

*Innovative
Fall Protection*

A permanent anchor point designed for use on timber structures, the Rafter**Link** can be purchased in a variety of configurations suitable for positioning on the top, side and ridge of a timber rafter.

The Rafter**Link** complete unit includes Safety**Link's** patented Standard Eyebolt. The Standard Eyebolt is designed for fall arrest, it's long tapered stem is designed to absorb energy while arresting a fall therefore reducing the load off the structure and the person attached to the anchor. The length of the eyebolt also enables the eyebolt to protrude above the roof structure when installing into timber structures.

Safety**Link's** patented Abseil Eyebolt can also be adapted to the Rafter**Link** forming an anchor from where you can abseil, creating a safe work station for hard to get to maintenance on buildings.

*Safety**Link's** roof anchors are multi-directional. A fall is never an anticipated event when working at heights, therefore the direction of your fall cannot be accurately predicted. All Safety**Link** roof anchors are designed and tested as multi-directional.*

Benefits of choosing Safety**Link**:

Safety**Link's** rafter mounted roof anchors are designed for use on timber rafters with metal or tiled roofs. Our unique designed roof anchors provide restraint and fall arrest safety for residential, commercial and industrial building sites.

Safety**Link's** roof anchors patented designs absorb energy, which means if in the event of a fall the anchors absorb the energy, reducing risk of injury to the person and damage to the structure.

Safety**Link's** designs represent a perfect engineered solution for working at heights and roof safety fall protection.

- 🔗 Multi-directional fall protection.
- 🔗 Single person anchor.
- 🔗 Rated at 15kN.

Safety**Link** will provide you with the following:

- 🔗 All products tested and manufactured to Australian and New Zealand Standards.
- 🔗 All distributors and installers are trained to use Safety**Link** products.
- 🔗 Supply installation guides, testing results and product sheets.
- 🔗 Products tested using a qualified and reputable testing authority.
- 🔗 Supply a large range of roof anchors that protect you from the ground up, allowing complete access to your roof.
- 🔗 Installers are qualified to do yearly inspections on your anchors as per Australian and New Zealand Standards.



SafetyLink®

*Innovative
Fall Protection*

SafetyLink Pty Ltd 1300 789 545

+61 2 4964 1068 info@safetylink.com

For further information and to order our products visit our website.

***'Innovative
Fall Protection'***

www.safetylink.com