

RAFTERLINK

Timber Rafter Mounted Anchor



Terms and Conditions



Website



- The RafterLink complete unit includes SafetyLink's patented Eyebolt. The length of the eyebolt enables to protrude above the roof structure when installing into timber structures.
- Standard Eyebolt is designed for fall arrest, it's long tapered stem is designed to absorb energy while arresting a fall therefore reducing the load off the structure and the person attached to the anchor.

WHAT AM I USED FOR?

A height safety anchor point designed for use on timber structures where there is easy access to the top of the rafter. Designed with unique energy absorbing capabilities, to reduce the risk of injury to the person and damage to the structure.

STANDARDS

Complies with AS/NZS 1891.4.

Product Parts	Description	Qty	Weight	Material
WASHER 75mm Square	Rubber Hat Washer 75mm	1	.035g	Rubber
RAFTER-BASE	RafterLink 0 Degree Pitch	1	1.105g	Stainless Steel
EYEBOLT-STANDARD	Standard Eyebolt	1	.263g	316 Stainless Steel
NUT LOCKING HEX	M16 Locking Hex Nut	1	.039g	316 Stainless Steel
			1.442g	



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on <u>ip@safetylink.com</u> and quote the product code.

Version 05.18