





# RAFTERLINK

# Side Mounted Timber Rafter Mounted Anchor



- The RafterLink complete unit includes SafetyLink's patented Eyebolt. The length of the
  eyebolt enables to protrude above the roof structure when installing into timber
  structures.
- Standard Eyebolt is designed for fall arrest, it's long tapered stem is designed to absorb
  energy while arresting a fall therefore reducing the load off the structure and the person
  attached to the anchor.

## WHAT AM I USED FOR?

An anchor point designed for use on timber structures where there is easy access to the underside of the roof. Installs onto the side of the rafter.

#### **STANDARDS**

Complies with AS/NZS 1891.4.

| COMPLETE UNIT - PRODUCT CODE: RAFTR004 |                         |     |        |                     |
|--|-------------------------|-----|--------|---------------------|
| Product Parts                          | Description             | Qty | Weight | Material            |
| WASHER 75mm Square                     | Rubber Hat Washer 75mm  | 1   | .035g  | Rubber              |
| RAFTER-BASE-SIDE                       | RafterLink with adapter | 1   | 1.346g | Stainless Steel     |
| EYEBOLT-STANDARD                       | Standard Eyebolt        | 1   | .263g  | 316 Stainless Steel |
| NUT LOCKING HEX                        | M16 Locking Hex Nut     | 1   | .039g  | 316 Stainless Steel |
|  |                         |     | 1.683g |                     |



### © 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on <a href="mailto:ip@safetylink.com">ip@safetylink.com</a> and quote the product code.

Version 05.18