



Conditions



Website

ABSEIL EYEBOLT



- Available to attach to a multitude of differing bases for differing structures (not to be used with surface mounted anchor).
- Unique energy absorbing capabilities, protecting structures and users in the event of a fall.
- Abseiling eyebolts are to be used for rope access (<u>abseiling and fall arrest</u>).

STANDARDS

Complies with AS/NZS 1891.4.

WHAT AM I USED FOR?

The **Abseiling Eyebolt** is a fall arrest anchor which uses the same tapered design as the standard eyebolt but incorporates a shorter shaft enabling the eyebolt to withstand a live load without activating the bending motion that occurs when arresting a fall.

POSITIONING OF SAFETYLINK ANCHOR POINT

(refer to appendix diagram of the Installation Handbook)

The first Anchor Point must be in a position easily and safely reached by a secured ladder or a manhole access point. All safety procedures must be complied with in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety protection system.

COMPLETE UNIT - PRODUCT CODE: EYEBT002				
Product Parts	Description	Qty	Weight	Material
EYEBOLT-ABSEIL	Abseil Eyebolt	1	.220g	316 Stainless Steel
NUT M16	Nut: M16	1	.029g	316 Stainless Steel
			.249g	



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Version 05.18